

High Pressure Air Compressors



Airpac Bukom
Oilfield Services



1050 scfm (365 psig) High Pressure Safe Area XRVS Air Compressor

Airpac Bukom's range of XRVS High Pressure Air Compressors produce volumes of 29.7m³/min (1050 scfm) with delivered pressure of 25.1 barg (365 psig).

The range is fitted with battery, spark arrestors and over-speed protection to safe area specification.

Emergency Shutdown (ESD) is available on all models to provide instant shutdown in the event of gas detection or similar hazards.

When supplied as a package with booster compressors and air dryers they are ideal for pipeline dewatering and drying projects as well as LNG Module & Pipework Testing. Airpac Bukom provide a full range of ancillary equipment to ensure air quality to appliance requirement.

Airpac Bukom's continuous upgrade and enhancement programme ensures longevity and operational efficiency.

Features

- Delivered air quality is to ISO 1217 - international standard
- Low engine oil shutdown
- Chalwyn overspeed device
- High engine water temperature shutdown
- High compressor oil temperature shutdown
- Spark arrestors
- Emergency stop button
- Fuel shut off valve
- Electric starter
- Anti-static fan belts
- Skid mounted

Options

- Experienced personnel providing a complete operational package including: hook-up & commissioning, servicing, re-fuelling and multiple installation assistance
- Pressure reducing and non return valves
- Pressure maintaining valve

Technical Specifications

1050 scfm (365 psig) High Pressure Safe Area XRVS Air Compressor

Performance

Model	1050 scfm (365 psig) XRVS Air Compressor
Delivered Flow	1050 scfm 29.7m ³ /min
Delivered Pressure	365 psig 25.1 barg
Discharge Temperature	Ambient +10°C
Sound Power Level	83dBa @ 9.8 metres
Fuel Consumption	64.9 litres per hour
Fuel Tank Capacity	796 litres
Max. Working Ranges	-10°C to +50°C
Pneumatic/Battery Start	Battery
Outlet Connection	1 no 2" Fig 200 Weco Union
Caged/Containerised/Mounted	Skid Mounted

Weights & Dimensions

	Metric	Imperial
Overall Length	4350mm	171"
Overall Width	2150mm	85"
Overall Height	2440mm	96"
Weight	6260 Kgs	13801 lbs

N.B. Weights and dimensions are for guidance only; please contact your local Airpac Bukom office for individual asset details

E. & O.E.

© Airpac Bukom Oilfield Services 2018
A division of Vp plc



Airpac Bukom Oilfield Services UK is certified to
BS EN ISO 9001:2015 & BS EN ISO 14001:2015



Aberdeen, UK
t: +44 (0) 1467 242 000
e: airpac.europe@vpplc.com

Great Yarmouth, UK
t: +44 (0) 1493 652 732
e: airpac.europe@vpplc.com

Singapore
t: +65 6861 5961
e: airpac.asia@vpplc.com

Australia
t: +61 8 9418 2177
e: airpac.australia@vpplc.com

Sharjah, U.A.E.
t: +44 (0) 1493 652 732
e: airpac.me@vpplc.com

Curaçao, Dutch Caribbean
t: +5999 8682599
e: airpac.americas@vpplc.com