

Safe Area Air Compressors



Airpac Bukom
Oilfield Services



950 scfm (175 psig) Safe Area XAHS Air Compressor

Airpac Bukom's XAHS 950 scfm Safe Area Air Compressor offers delivered flow of 26.9m³/min (950 scfm) with a pressure rating of up to 12 barg (175 psig).

The skid mounted product is fitted with battery start, spark arrestors and overspeed protection to safe area specification. Emergency Shutdown (ESD) is available on all models to provide instant shutdown in the event of gas detection or similar hazards.

Our continuous upgrade and product enhancement programme ensures longevity and operational efficiency.

We can provide a full range of ancillary equipment, available to ensure air quality to project requirements.

Features

- Delivered air quality is to ISO 1217 - international standard
- Low engine oil shutdown
- Chalwyn overspeed device
- High engine water temperature shutdown
- High compressor oil temperature shutdown
- Spark arrestors
- Emergency stop button
- Fuel shut off valve
- Electric starter
- Anti-static fan belts
- Skid mounted

Options

- Experienced offshore engineering personnel offering machine service re-fuelling and multiple installation assistance
- Pressure reducing and non return valves
- Pressure maintaining valve

Technical Specifications

950 scfm (175 psig) Safe Area XAHS Air Compressor

Performance

| Model | 950 scfm (175 psig) XAHS Air Compressor |
|-------------------------|---|
| Delivered Flow | 950 scfm 26.9m ³ /min |
| Delivered Pressure | 175 psig 12 barg |
| Discharge Temperature | Ambient +10°C |
| Sound Power Level | 100dBa |
| Fuel Consumption | 44.8 litres per hour |
| Fuel Tank Capacity | 580 litres |
| Max. Working Ranges | -10°C to +50°C |
| Pneumatic/Battery Start | Battery |
| Outlet Connection | 1 no 2" Fig 200 Weco Union |
| Caged/Mobile/Mounted | Skid Mounted |

Weights & Dimensions

| | Metric | Imperial |
|----------------|----------|-----------|
| Overall Length | 4350mm | 171" |
| Overall Width | 2150mm | 85" |
| Overall Height | 2440mm | 96" |
| Weight | 5700 Kgs | 12566 lbs |

E. & O.E.

© Airpac Bukom Oilfield Services 2017
A division of Vp plc



Airpac Bukom Oilfield Services UK is certified to
BS EN ISO 9001:2015 & BS EN ISO 14001:2015



Supplier No. 10044388

Aberdeen, UK
t: +44 (0) 1467 242 000
e: airpac.europe@vpplc.com

Great Yarmouth, UK
t: +44 (0) 1493 652 732
e: airpac.europe@vpplc.com

Singapore
t: +65 6861 5961
e: airpac.asia@vpplc.com

Australia
t: +61 8 9418 2177
e: airpac.australia@vpplc.com

Sharjah, U.A.E.
t: +44 (0) 1493 652 732
e: airpac.mea@vpplc.com

Curaçao, Dutch Caribbean
t: +5999 8682599
e: airpac.americas@vpplc.com