



1800 scfm (377 psig) DD 1800 Multi Pressure Desiccant Dryer

If high pressure, quality clean dry compressed air is a process or project requirement, Airpac Bukom can provide a range of high pressure desiccant dryers sized to meet their primary compressor fleet.

The DD 1800 unit produces air volumes of 33.9m³/min (1200 scfm) to 50.9m³/min (1800 scfm) at pressures ranging from 7 barg (101 psig) to 26 barg (377 psig).

Mounted in a certified lifting frame for transport and protection, Airpac Bukom's range of high pressure desiccant dryers are a complete package, incorporating:

- A twin tower heatless adsorbent dryer unit
- Integral aftercooler with condensate separator and auto drain
- Two stage oil removal filtration with auto drains and final dust filter
- Back pressure maintaining valve

Technical Specifications

1800 scfm (377 psig) DD 1800 Multi Pressure Desiccant Dryer

Performance

Model	7 - 10 barg	24- 26 barg
Volume Dependant on Working Pressure	1200 scfm @ 101-145 psig 33.9m ³ /min @ 7-10 barg	1800 scfm @ 348-377 psig 50.9m ³ /min @ 24-26 barg
Residual Oil Content @ 20°C	0.01mgs/m ³ / 0.008 ppm w/w	
Discharge Temperature	Ambient +10 °C	
Pressure Dewpoint	-40°C to -60°C	
Inlet / Outlet Connections	2" BSP	

Weights & Dimensions

	Metric	Imperial
Overall Length	3400mm	134"
Overall Width	2470mm	97"
Overall Height	2200mm	87"
Weight	7300 Kgs	16094 lbs

E. & O.E.

© Airpac Bukom Oilfield Services 2017
A division of Vp plc



Airpac Bukom Oilfield Services UK is certified to
BS EN ISO 9001:2015 & BS EN ISO 14001:2015



Aberdeen, UK
t: +44 (0) 1467 242 000
e: airpac.europe@vpplc.com

Great Yarmouth, UK
t: +44 (0) 1493 652 732
e: airpac.europe@vpplc.com

Singapore
t: +65 6861 5961
e: airpac.asia@vpplc.com

Australia
t: +61 8 9418 2177
e: airpac.australia@vpplc.com

Sharjah, U.A.E.
t: +44 (0) 1493 652 732
e: airpac.me@vpplc.com

Curaçao, Dutch Caribbean
t: +5999 8682599
e: airpac.americas@vpplc.com