



2800 scfm (350 psig) Multi Pressure Desiccant Dryer

If high quality clean dry compressed air is a process or project requirement, Airpac Bukom can provide a range of desiccant dryers sized to meet their primary compressor fleet.

The unit produces air volumes of 34m³/min (1200 scfm) to 79.3m³/min (2800 scfm) to pressures ranging from 10 barg (150 psig) to 24 barg (350 psig).

Mounted in a certified lifting frame for transport and protection, Airpac Bukom's range of desiccant dryers are a complete package, incorporating:

- A twin tower heatless adsorbent dryer unit
- Integral aftercooler with condensate separator and auto drain
- Double oil removal filtration with auto drains and final dust filter

Technical Specifications

2800 scfm (350 psig) Multi Pressure Desiccant Dryer

Performance

Model	10 barg	24 barg
Volume Dependant on Working Pressure	1200 scfm @ 150 psig 34m ³ /min @ 10 barg	2800 scfm @ 350 psig 79.3m ³ /min @ 24 barg
Residual Oil Content @ 20°C	0.03mgs/m ³	
Discharge Temperature	Ambient +10 °C	
Pressure Dewpoint	-40°C	
Inlet / Outlet Connections	2" Fig 100 Weco Union	

Weights & Dimensions

	Metric	Imperial
Overall Length	5500mm	217"
Overall Width	1800mm	71"
Overall Height	2900mm	114"
Weight	7250 Kgs	15984 lbs

E. & O.E.

© Airpac Bukom Oilfield Services 2017
A division of Vp plc



Airpac Bukom Oilfield Services UK is certified to
BS EN ISO 9001:2015 & BS EN ISO 14001:2015



Aberdeen, UK
t: +44 (0) 1467 242 000
e: airpac.europe@vpplc.com

Great Yarmouth, UK
t: +44 (0) 1493 652 732
e: airpac.europe@vpplc.com

Singapore
t: +65 6861 5961
e: airpac.asia@vpplc.com

Australia
t: +61 8 9418 2177
e: airpac.australia@vpplc.com

Sharjah, U.A.E.
t: +44 (0) 1493 652 732
e: airpac.me@vpplc.com

Curaçao, Dutch Caribbean
t: +5999 8682599
e: airpac.americas@vpplc.com