



Oil Removal Filters

Oil content of the compressed air can be controlled to $0.01\text{mg}/\text{m}^3$ through Airpac Bukom's range of oil removal filters. These free standing units are housed in a lifting frame for ease of transport and protection on site.

The volume range is $12\text{m}^3/\text{min}$ (423 scfm) to $142\text{m}^3/\text{min}$ (5040 scfm) with a pressure range from 7 barg (100 psig) to 250 barg (3625 psig). The housing material used determines both pressure and output.

Technical Specifications

Oil Removal Filters

Performance

Model	Oil Removal Filter HP	Oil Removal Filter VHP
Volume Dependant on Working Pressure	423 scfm @ 100 psig 12m ³ /min @ 7 barg or 3390 scfm @ 928 psig 96m ³ /min @ 64 barg	423 scfm @ 100 psig 12m ³ /min @ 7 barg or 5085 scfm @ 3625 psig 144m ³ /min @ 250 barg
Residual Oil Content @ 20°C	0.01mgs/m ³	
Discharge Temperature	Ambient +10°C	
Inlet / Outlet Connections	2" NPT	

Weights & Dimensions

	Metric	Imperial
Overall Length	1500mm	59"
Overall Width	600mm	24"
Overall Height	1000mm	39"
Weight	350 Kgs	771 lbs

E. & O.E.

© Airpac Bukom Oilfield Services 2017
A division of Vp plc



Airpac Bukom Oilfield Services UK is certified to
BS EN ISO 9001:2015 & BS EN ISO 14001:2015



Aberdeen, UK
t: +44 (0) 1467 242 000
e: airpac.europe@vpplc.com

Great Yarmouth, UK
t: +44 (0) 1493 652 732
e: airpac.europe@vpplc.com

Singapore
t: +65 6861 5961
e: airpac.asia@vpplc.com

Australia
t: +61 8 9418 2177
e: airpac.australia@vpplc.com

Sharjah, U.A.E.
t: +44 (0) 1493 652 732
e: airpac.me@vpplc.com

Curaçao, Dutch Caribbean
t: +5999 8682599
e: airpac.americas@vpplc.com