

Sand Collection Box



Airpac Bukom
Oilfield Services



Sand Collection Box

Sand Collection Box and filtration system for use in conjunction with Airpac Bukom Sand Filtration Units.

Two screens are positioned at the front of the sand box so the rejected product from the Sand Filtration Unit can be separated.

Sand is filtered from the water and easily removed by the operator, the recovered water can then be removed.

Features

- Standard 200 Micron screens supplied
- DNV 2.7-1 lifting specification
- 2" 1502 inlet connection
- 2" 206 Weco outlet
- Vented Flame Arrestor

Options

- A range of Micron screens ranging from 50 - 800 Micron are available on request

Technical Specifications

Sand Collection Box

Performance

Model	Sand Collection Box
Filter Mesh	Standard 2 x 200 Micron screens
Inlet Connection	2" x 1502 Weco Union
Outlet Connection	2" x 206 Weco Union
Flush Line Hose	2" 1502 M/F Weco Union Length 15 meters MWP 580 psi
Lifting Certification	DNV 2.7-1
Forklift Pockets	Yes
Flame Arrestor	2" Flame Arrestor fitted to vent

Weights & Dimensions

	Metric	Imperial
Length	1732mm	68"
Width	1902mm	75"
Height	1413mm	56"
Weight	1100 Kgs	2425 lbs

E. & O.E.

© Airpac Bukom Oilfield Services 2017
A division of Vp plc



Airpac Bukom Oilfield Services UK is certified to
BS EN ISO 9001:2015 & BS EN ISO 14001:2015



Supplier No. 10044388

Aberdeen, UK
t: +44 (0) 1467 242 000
e: airpac.europe@vpplc.com

Great Yarmouth, UK
t: +44 (0) 1493 652 732
e: airpac.europe@vpplc.com

Singapore
t: +65 6861 5961
e: airpac.asia@vpplc.com

Australia
t: +61 8 9418 2177
e: airpac.australia@vpplc.com

Sharjah, U.A.E.
t: +44 (0) 1493 652 732
e: airpac.me@vpplc.com

Curaçao, Dutch Caribbean
t: +5999 8682599
e: airpac.americas@vpplc.com