



Sand Filter



Tool Box

10,000 psig - 15,000 psig Dual Pot Sand Filters

Airpac Bukom's rental fleet of 10,000 psig and 15,000 psig dual pot sand filters improve well analysis during testing operations through the effective removal of sand and other solids from the well effluent. Wellhead sand filtration is established as an industry standard technique for sand and solids removal.

The two filtration pods are controlled individually allowing for either single or dual pot operation. Normally, one vessel is in use, in order to facilitate cleaning of the other.

The unit is skid mounted in a DNV 2.7-1 cage, complete with inlet and outlet manifolding, double gate valves on the downstream side and connections to register differential pressure across filters.

Each sand filter is supplied with an extensive spares package and fully equipped tool box.

Advantages

- Minimum mesh size 50 Micron
- Filter collapse pressure Maximum OD 14¼ inch
- Gas flow capacity 5,000 psig up to 20 MM scf/d 10,000 psig up to 35 MM scf/d 15,000 psig up to 50 MM scf/d
- Liquid flow capacity up to 5,000 Bpd

Flow capacity is dependent on filter element mesh size, viscosity and the amount of pollution. The filter elements are designed to stop sand/debris transport, without obstructing liquid and or gas flow through the unit.

Features

- Modular and rugged filter design
- Standard 200 micron filter cartridge supplied
- Annular flow and sand storage
- Safe & quick cleaning features
- Vertically positioned gate valves (to avoid gate obstruction)
- Fitted with back up valves
- No post-frac clean up required, production starts immediately through the facilities
- Diaphragm pump to facilitate flushing of the filter elements
- Tool box container supplied with critical spares and work space for operators

Options

- Experienced personnel providing a complete operational package including: hook-up & commissioning, servicing, re-fuelling and multiple installation assistance
- A range of micron screen sizes are available
- Can be supplied with a Sand Collection Box for collection of the waste solids
- High pressure bleed hoses are available on request

Technical Specifications

5,000 psig - 15,000 psig Dual Pot Sand Filters

Performance

Model	10,000 psig	15,000 psig
Working Pressure	10,000 psig	15,000 psig
Flow-line connections	3 1/16" Flange	3 1/16" Flange
Gas Flow capacity <small>(higher rates may be achievable if modelling conducted)</small>	35 MM scf/d	50 MM scf/d
Liquid flow capacity	5,000 Bpd	5,000 Bpd
Holding capacity per vessel	180 effect litres	100 litres
Vessel O.D	Up to 356mm / 14"	356mm / 14"
Filter Element O.D	114 mm / 4 1/2"	165mm / 6 1/2"
Filter mesh sizes (wire screen)	50 - 800 microns	
Differential Pressure Across the Filter Element	1 barg (clean and empty) in use advised max. ± 25 barg	
Filter Collapse Pressure	<100 barg	180 barg
Inlet Connection	3" 1502 Weco Union	4" 2202 Weco Union
Flush Line Inlet	2" 1502 Weco Union	n/a
Flush Line Outlet	2" 1502 Weco Union (x2)	2" 2202 Weco Union (x1)
Temperature class	Standard up to 250°F / 121°C	
Design Code	ASME & API 6A Certification Authority Det Norske Veritas	
Service	Sour (H ₂ S) service, Per NACE MR-01-75 latest rev.	

Weights & Dimensions

*Sand Filter	10,000 psig	15,000 psig
Overall Length <small>(operational)</small>	2680mm / 105.5"	2500mm / 98"
Overall Width <small>(operational)</small>	2400mm / 94"	2500mm / 98"
Overall Height <small>(operational)</small>	4200mm / 165" <small>(with lifting beams extended max. 7500mm)</small>	4300mm / 169" <small>(with lifting beams extended max. 7500mm)</small>
Weight	9500 Kgs / 20944 lbs	15000 Kgs / 33069 lbs
Tool Box	Metric	Imperial
Dimensions	(L)1829 x (W)1524 x (H)2438mm	(L) 72" x (W) 60" x (H) 96"
Weight	6000 Kgs	13228 lbs

* Sand Filtration Units must be [transported horizontally](#).

Transportation dimensions for 5K & 10K (L) 4200mm x (W) 2400mm x (H) 2680mm
Transportation dimensions for 15K (L) 4300mm x (W) 2500mm x (H) 2500mm

E. & O.E.

© Airpac Bukom Oilfield Services 2017
A division of Vp plc



Airpac Bukom Oilfield Services UK is certified to BS EN ISO 9001:2015 & BS EN ISO 14001:2015



Supplier No. 10044388

Aberdeen, UK
t: +44 (0) 1467 242 000
e: airpac.europe@vpplc.com

Great Yarmouth, UK
t: +44 (0) 1493 652 732
e: airpac.europe@vpplc.com

Singapore
t: +65 6861 5961
e: airpac.asia@vpplc.com

Australia
t: +61 8 9418 2177
e: airpac.australia@vpplc.com

Sharjah, U.A.E.
t: +44 (0) 1493 652 732
e: airpac.me@vpplc.com

Curaçao, Dutch Caribbean
t: +5999 8682599
e: airpac.americas@vpplc.com